



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant DL380 G5 (2.66GHz, Intel Xeon processor 5150)

SPECfp2000 = **2824**  
SPECfp\_base2000 = **2597**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jul-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	40.9	3915	40.9	3915
171.swim	3100	109	2855	105	2955
172.mgrid	1800	100	1794	78.3	2300
173.applu	2100	101	2089	75.2	2794
177.mesa	1400	50.4	2778	46.4	3017
178.galgel	2900	46.6	6229	46.6	6229
179.art	2600	25.2	10337	25.2	10337
183.quake	1300	57.4	2267	47.0	2767
187.facerec	1900	67.9	2799	51.6	3681
188.amp	2200	113	1952	113	1952
189.lucas	2000	96.7	2067	96.0	2083
191.fma3d	2100	104	2024	104	2024
200.sixtrack	1100	108	1019	108	1019
301.apsi	2600	162	1603	156	1665

### Hardware

CPU: Intel Xeon processor 5150 (2.66GHz, 4MB L2 shared, 1333MHz bus)  
CPU MHz: 2660  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip  
CPU(s) orderable: 1,2 chips  
Parallel: No  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 4 MB I+D on chip per chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 16 GB (8x2048 MB PC2-5300F)  
Disk Subsystem: 1x36 GB 10 K SAS  
Other Hardware:

### Software

Operating System: RedHat Enterprise Linux 4.0 Advanced Server for AMD64/EM64T, Update 3 Kernel 2.6.9-34.EL  
Compiler: Intel C++ Compiler for EM64T-based applications, (Version 9.1 Build 20060323)  
Intel Fortran Compiler for EM64T-based applications, (Version 9.1 Build 20060323)  
PathScale EKOPATH(TM) Compiler Suite, Release 2.4  
File System: ext2  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1= -prof_gen PASS2=-prof_use (Intel Compiler)
+FDO: PASS1= -fb_create fbdata PASS2=-fb_opt fbdata (PathScale Compiler)
ifort is the Intel Fortran compiler, icc is the Intel C++ compiler; and
pathf95 is PathScale Fortran compiler, pathcc is the PathScale C compiler.
Base tuning for C programs: icc -fast -auto_ilp32 +FDO
Base tuning for FORTRAN programs: ifort -fast +FDO
Portability:
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI
Peak tuning:
168.wupwise: basepeak=1
171.swim: pathf95 -Ofast -LNO:fusion=2:simd=0 -WOPT:val=0 -march=em64t
172.mgrid: pathf95 -Ofast -CG:load_exe=0 -LNO:blocking=off:prefetch_ahead=5
-OPT:ro=3:unroll_size=256 -WOPT:mem_opnds=on -march=em64t
173.applu: pathf95 -O3 -ipa -CG:load_exe=0
-LNO:fission=1:fusion=2:blocking=off:full_unroll_size=9000
-OPT:IEEE_a=3:ro=3 -TENV:X=3 -march=em64t
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant DL380 G5 (2.66GHz, Intel Xeon processor 5150)

SPECfp2000 = 2824  
SPECfp\_base2000 = 2597

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jul-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

```
177.mesa: pathcc -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
          -GRA:optimize_boundary=on -march=em64t +FDO
178.galgel: basepeak=1
179.art: basepeak=1
183.quake: icc -fast +FDO ONESTEP=yes -rcd -auto-ilp32
187.facerec: pathf95 -Ofast -IPA:plimit=1500 -LNO:fusion=2
            -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 -march=em64t +FDO
188.ammmp: basepeak=1
189.lucas: ifort -fast ONESTEP=yes
191.fma3d: basepeak=1
200.sixtrack: basepeak=1
301.apsi: pathf95 -Ofast -CG:load_exe=0 -LNO:opt=0:prefetch=1 -march=em64t
```

BIOS Configuration Notes  
Power Regulator set to Static High Performance Mode

Other Configuration Notes  
Single processor kernel used