



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL580 G4 (3.4GHz, Intel Xeon processor 7140M)

SPECfp_rate2000 = 105
SPECfp_rate_base2000 = 105

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Aug-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	16	254	117	16	254	117
171.swim	16	1070	53.8	16	1070	53.8
172.mgrid	16	637	52.4	16	637	52.4
173.applu	16	707	55.1	16	707	55.1
177.mesa	16	201	129	16	198	131
178.galgel	16	149	361	16	149	361
179.art	16	100	482	16	100	482
183.quake	16	318	76.0	16	317	76.1
187.facerec	16	259	136	16	255	138
188.amp	16	307	133	16	316	129
189.lucas	16	690	53.8	16	691	53.7
191.fma3d	16	581	67.1	16	581	67.1
200.sixtrack	16	273	74.9	16	275	74.1
301.apsi	16	385	125	16	385	125

Hardware

CPU: Intel Xeon processor 7140M (800MHz system bus)
CPU MHz: 3400
FPU: Integrated
CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1,2,4 chips
Parallel: No
Primary Cache: 12 K I micro-ops + 16 KB D on chip per core
Secondary Cache: 1 MB I+D on chip per core
L3 Cache: 16 MB on chip per chip
Other Cache: N/A
Memory: 32 GB (16x2048MB PC2-3200 dual-rank)
Disk Subsystem: 1x36 GB 10 K SAS
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Intel Fortran Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for Fortran programs: -fast -Qansi_alias +FDO

Base tuning for C programs: -fast +FDO shlw32M.lib

Portability flags:

178.galgel: -FI /F32000000

Peak tuning:

168.wupwise: -fast -Qansi_alias +FDO

171.swim: -fast +FDO ONESTEP=yes

172.mgrid: -fast -Qansi_alias +FDO

173.applu: basepeak=1

177.mesa: -fast +FDO ONESTEP=yes

178.galgel: basepeak=1

179.art: basepeak=1

183.quake: -fast -Oa -Qrcd +FDO ONESTEP=yes shlw32M.lib

187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO ONESTEP=yes

188.amp: -fast -Qansi_alias +FDO



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL580 G4 (3.4GHz, Intel Xeon processor 7140M)

SPECfp_rate2000 = 105
SPECfp_rate_base2000 = 105

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

189.lucas: -fast
191.fma3d: basepeak=1
200.sixtrack: -fast +FDO
301.apsi: basepeak=1
BIOS Configuration Notes
Hyper-Threading Technology enabled