



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY Econel100, Intel Pentium D processor 925, 3.0 GHz

SPECfp_rate2000 = 37.1

SPECfp_rate_base2000 = 37.1

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Oct-2006 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	62.0	59.8	2	62.0	59.8
171.swim	2	212	33.9	2	212	33.9
172.mgrid	2	136	30.7	2	136	30.7
173.applu	2	167	29.2	2	167	29.2
177.mesa	2	88.6	36.7	2	88.6	36.7
178.galgel	2	96.5	69.7	2	96.5	69.7
179.art	2	52.9	114	2	52.9	114
183.quake	2	79.7	37.9	2	79.7	37.9
187.facerec	2	106	41.6	2	106	41.6
188.amp	2	179	28.5	2	179	28.5
189.lucas	2	142	32.8	2	142	32.8
191.fma3d	2	160	30.5	2	160	30.5
200.sixtrack	2	184	13.9	2	184	13.9
301.apsi	2	211	28.6	2	211	28.6

Hardware

CPU: Intel Pentium D processor 925 (3.0 GHz, 2x2MB L2, 800 MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops(I) + 16KB(D) on chip, per core
Secondary Cache: 2048KB(I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2048 MB DDRII-RAM PC2-4200E (CAS 4-4-4)
Disk Subsystem: Samsung SP2504C (SATA, 7.2krpm, 250GB)
Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
Kernel 2.6.5-7.244-smp on an x86_64
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
Build 20060120 (for 64-bit applications)
File System: ext3
System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
PASS1: -prof_gen PASS2: -prof_use

Optimization flags

ONESTEP=yes set for all benchmarks

Portability flags

-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags

for Fortran and C programs: -fast +FDO

Peak tuning flags

same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY Econel100, Intel Pentium D processor 925, 3.0 GHz

SPECfp_rate2000 = 37.1

SPECfp_rate_base2000 = 37.1

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Oct-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

The system bus runs at 800 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>