



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM System X 3105 (AMD Opteron (TM) 1216)

SPECfp2000 = 2059  
SPECfp\_base2000 = 1894

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Sep-2006 | Hardware Avail: Sep-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
168.wupwise	1600	61.7	2593	54.8	2921	[Bar chart showing ratio 2921]			
171.swim	3100	119	2612	109	2847	[Bar chart showing ratio 2847]			
172.mgrid	1800	109	1653	96.9	1858	[Bar chart showing ratio 1858]			
173.applu	2100	103	2042	94.3	2228	[Bar chart showing ratio 2228]			
177.mesa	1400	73.7	1899	69.2	2022	[Bar chart showing ratio 2022]			
178.galgel	2900	93.9	3090	95.1	3051	[Bar chart showing ratio 3051]			
179.art	2600	101	2576	74.8	3477	[Bar chart showing ratio 3477]			
183.quake	1300	81.5	1596	75.1	1730	[Bar chart showing ratio 1730]			
187.facerec	1900	77.2	2461	74.5	2550	[Bar chart showing ratio 2550]			
188.amp	2200	153	1437	147	1494	[Bar chart showing ratio 1494]			
189.lucas	2000	102	1953	88.4	2261	[Bar chart showing ratio 2261]			
191.fma3d	2100	130	1620	131	1604	[Bar chart showing ratio 1604]			
200.sixtrack	1100	137	802	130	843	[Bar chart showing ratio 843]			
301.apsi	2600	169	1540	157	1653	[Bar chart showing ratio 1653]			

### Hardware

CPU: AMD Opteron 1216  
 CPU MHz: 2400  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1 chip  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD (on chip) per core  
 Secondary Cache: 1024KB (I+D) (on chip) per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 4x1GB, PC2-5300  
 Disk Subsystem: SATA, 80GB 10K RPM  
 Other Hardware: None

### Software

Operating System: SuSE Linux 9.0 SP3 SLES 64 bit Kernel 2.6.5-7.244-smp  
 Compiler: PathScale EKO Compiler Suite, Release 2.4  
 PathScale EKOPATH(TM) Compiler Suite, Release 2.4  
 File System: Linux/reiserfs  
 System State: Multi-user, run level 3

## Notes/Tuning Information

+FDO: PASS1= -fb\_create fbdata PASS2= -fb\_opt fbdata

### Baseline optimization

C programs: -Ofast -WOPT:mem\_opnds=on +FDO  
 Fortran programs: -Ofast -LNO:fusion=2 -OPT:fast\_complex=on +FDO  
 Portability Flags:  
 178.galgel: -fixedform

### Peak Tuning:

168.wupwise: -Ofast -IPA:linear=on -LNO:prefetch Ahead=5:prefetch=3  
 -OPT:unroll\_times\_max=8:unroll\_size=128:IEEE\_NaN\_Inf=off:ro=3  
 171.swim: -Ofast -CG:local\_fwd\_sched=on -LNO:fusion=2 -m3dnow  
 172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE\_arith=3:unroll\_size=200  
 -LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2  
 -WOPT:mem\_opnds=on:aggstr=0  
 173.applu: -Ofast -CG:local\_fwd\_sched=on -OPT:ro=3 -TENV:X=3  
 -LNO:fusion=2:fission=2:full\_unroll\_size=10000 +FDO



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM System X 3105 (AMD Opteron (TM) 1216)

SPECfp2000 = 2059  
SPECfp\_base2000 = 1894

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Sep-2006 | Hardware Avail: Sep-2006 | Software Avail: Mar-2006

## Notes/Tuning Information (Continued)

```

177.mesa:      -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on -WOPT:mem_opnds=on +FDO
178.galgel:    -Ofast -OPT:fast_complex=on +FDO
179.art:       -O3 -OPT:Ofast -fno-math-errno -mno-sse2 -m32
183.quake:    -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec:  -Ofast -IPA:plimit=1500 -LNO:fusion=2
              -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 +FDO
188.amp:      -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
              -GRA:optimize_boundary=on -fno-math-errno -TENV:X=4 +FDO
189.lucas:    -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d:    -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
              -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:early_intrinsics=on
              -fno-math-errno -CG:load_exe=1 +FDO
301.apsi:     -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```