



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System X 3105 (AMD Opteron (TM) 1214)

SPECint_rate2000 = 35.0
SPECint_rate_base2000 = 31.3

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Sep-2006 | Hardware Avail: Sep-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	105	31.0	2	105	31.0
175.vpr	2	132	24.7	2	127	25.6
176.gcc	2	71.9	35.5	2	71.7	35.6
181.mcf	2	326	12.8	2	200	20.9
186.crafty	2	52.7	44.0	2	52.5	44.2
197.parser	2	175	23.9	2	140	29.9
252.eon	2	56.2	53.7	2	49.4	61.1
253.perlbnk	2	122	34.1	2	108	38.8
254.gap	2	77.6	32.9	2	77.6	32.9
255.vortex	2	88.0	50.1	2	81.9	53.8
256.bzip2	2	122	28.5	2	122	28.5
300.twolf	2	251	27.7	2	195	35.6

Hardware

CPU: AMD Opteron 1214
 CPU MHz: 2200
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip) per core
 Secondary Cache: 1024KB (I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x1GB, PC2-5300
 Disk Subsystem: SATA, 80GB 10K RPM
 Other Hardware: None

Software

Operating System: SuSE Linux 9.0 SP3 SLES 64 bit Kernel 2.6.5-7.244-smp
 Compiler: PathScale EKO Compiler Suite, Release 2.4
 PathScale EKOPATH(TM) Compiler Suite, Release 2.4
 File System: Linux/reiserfs
 System State: Multi-user, run level 3

Notes/Tuning Information

+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata

Baseline optimization flags:

C programs: -Ofast +FDO
 C++ programs: -Ofast +FDO

Portability Flags:

186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST
 253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
 -DSPEC_CPU2000_LP64
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
 -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
 255.vortex: -DSPEC_CPU2000_LP64

Peak Tuning:

164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
 175.vpr: -O3 -ipa -m32 +FDO
 176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
 181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3105 (AMD Opteron (TM) 1214)

SPECint_rate2000 = 35.0

SPECint_rate_base2000 = 31.3

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Sep-2006 | Hardware Avail: Sep-2006 | Software Avail: Mar-2006

Notes/Tuning Information (Continued)

```
186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon: -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
-OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
-LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbmk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
-fno-math-errno -IPA:plimit=10000 +FDO
254.gap: basepeak = true
255.vortex: -Ofast -OPT:goto=off -CG:p2align=on
-GRA:optimize_boundary=on -IPA:min_hotness=120 +FDO
256.bzip2: basepeak = true
300.twolf: -O2 -CG:gcm=off:p2align_freq=100000
-OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
-WOPT:mem_opnds=on -m32 +FDO
```