



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Acer Altos R520 (2.0 GHz Intel Xeon Processor 5130)

SPECint_rate2000 = 44.7
SPECint_rate_base2000 = 44.6

SPEC license #: 97 Tested by: Acer Incorporated Test date: Aug-2006 Hardware Avail: Nov-2006 Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	115	28.3	2	115	28.3
175.vpr	2	99.5	32.6	2	97.8	33.2
176.gcc	2	50.4	50.6	2	50.4	50.6
181.mcf	2	88.2	47.3	2	88.2	47.3
186.crafty	2	54.7	42.4	2	54.7	42.4
197.parser	2	116	35.9	2	116	36.0
252.eon	2	50.4	59.8	2	50.0	60.4
253.perlbnk	2	76.3	54.8	2	76.6	54.5
254.gap	2	56.5	45.1	2	56.5	45.1
255.vortex	2	59.8	73.7	2	59.8	73.7
256.bzip2	2	107	32.5	2	108	32.4
300.twolf	2	132	52.5	2	132	52.5

Hardware

CPU: Intel Xeon Processor 5130 (2.0 GHz, 4MB L2, 1333MHz system bus)
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip (per chip), shared
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 2048MB ECC FB-DIMM DDR2-667
Disk Subsystem: 1 x 73GB 10000RPM SAS HDD
Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790), Service Pack 1
Compiler: Intel C++ Compiler 9.1 Build 20060323Z for IA32
Microsoft Visual Studio .Net 2003 (7.1.3091, for libraries)
shlw32M.lib is SmartHeap Library Version 7.4 from http://www.microquill.com/
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: basepeak=yes
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: basepeak=yes
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
256.bzip2: -fast -Oa -Qunroll1 +FDO
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R520 (2.0 GHz Intel Xeon Processor 5130)

SPECint_rate2000 = 44.7

SPECint_rate_base2000 = 44.6

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Aug-2006 | Hardware Avail: Nov-2006 | Software Avail: Mar-2006

Notes/Tuning Information (Continued)

300.twolf: -fast +FDO shlw32M.lib

This result was measured on the Acer Alto R720.
The Altos R520 and Altos R720 are electronically equivalent.