



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R520 (1.86 GHz Intel Xeon Processor 5120)

SPECint_rate2000 = 80.7

SPECint_rate_base2000 = 80.7

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Aug-2006 | Hardware Avail: Nov-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	124	52.3	4	124	52.3
175.vpr	4	111	58.5	4	109	59.5
176.gcc	4	55.6	91.8	4	55.6	91.8
181.mcf	4	109	76.7	4	109	76.7
186.crafty	4	58.6	79.1	4	58.6	79.1
197.parser	4	127	65.8	4	126	66.0
252.eon	4	54.0	112	4	53.5	113
253.perlbnk	4	82.3	101	4	82.7	101
254.gap	4	65.5	77.9	4	65.5	77.9
255.vortex	4	66.2	133	4	66.2	133
256.bzip2	4	118	58.8	4	121	57.6
300.twolf	4	142	97.7	4	142	97.7

Hardware

CPU: Intel Xeon Processor 5120 (1.86 GHz, 4MB L2, 1066MHz system bus)
 CPU MHz: 1866
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 4096KB(I+D) on chip (per chip), shared
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 2048MB ECC FB-DIMM DDR2-667
 Disk Subsystem: 1 x 73GB 10000RPM SAS HDD
 Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790), Service Pack 1
 Compiler: Intel C++ Compiler 9.1 Build 20060323Z for IA32
Microsoft Visual Studio .Net 2003 (7.1.3091, for libraries)
 shlw32M.lib is SmartHeap Library Version 7.4 from http://www.microquill.com/
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: basepeak=yes
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: basepeak=yes
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
256.bzip2: -fast -Oa -Qunroll1 +FDO
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R520 (1.86 GHz Intel Xeon Processor 5120)

SPECint_rate2000 = 80.7

SPECint_rate_base2000 = 80.7

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Aug-2006 | Hardware Avail: Nov-2006 | Software Avail: Mar-2006

Notes/Tuning Information (Continued)

300.twolf: -fast +FDO shlw32M.lib

This result was measured on the Acer Alto R720.
The Altos R520 and Altos R720 are electronically equivalent.