



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML310 G4 (2.4 GHz, Intel Xeon processor 3060)

SPECint_rate2000 = **54.3**
SPECint_rate_base2000 = **54.1**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Oct-2006 Hardware Avail: Sep-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	95.2	34.1	2	95.2	34.1
175.vpr	2	84.8	38.3	2	82.0	39.6
176.gcc	2	41.4	61.7	2	41.4	61.7
181.mcf	2	71.6	58.3	2	71.6	58.3
186.crafty	2	45.7	50.8	2	45.7	50.8
197.parser	2	97.5	42.8	2	96.3	43.3
252.eon	2	41.4	72.8	2	41.6	72.5
253.perlbnk	2	63.5	65.8	2	63.2	66.1
254.gap	2	46.9	54.5	2	46.4	55.0
255.vortex	2	48.8	90.4	2	48.8	90.3
256.bzip2	2	85.8	40.5	2	85.8	40.5
300.twolf	2	109	63.8	2	109	63.8

Hardware

CPU: Intel Xeon processor 3060 (2.4GHz, 4MB L2 shared, 1066 MHz bus)
CPU MHz: 2400
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1 chip
Parallel: No
Primary Cache: 32 KB I+ 32 KB D on chip per core
Secondary Cache: 4 MB I+D on chip per chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4 GB (2x2 GB PC2-5300E)
Disk Subsystem: 1x80 GB SATA150
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Intel Fortran Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO ONESTEP=yes shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO ONESTEP=yes
Portability flags:
 176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast +FDO ONESTEP=yes
175.vpr: -fast +FDO ONESTEP=yes
176.gcc: basepeak=1
181.mcf: -fast +FDO ONESTEP=yes shlw32M.lib
186.crafty: -fast -Oa +FDO ONESTEP=yes shlw32M.lib
197.parser: -fast +FDO ONESTEP=yes
252.eon: -fast +FDO
253.perlbnk: -fast -Oa +FDO ONESTEP=yes shlw32M.lib
254.gap: -fast +FDO ONESTEP=yes
255.vortex: -fast +FDO ONESTEP=yes shlw32M.lib
256.bzip2: basepeak=1
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML310 G4 (2.4 GHz, Intel Xeon processor 3060)

SPECint_rate2000 = 54.3
SPECint_rate_base2000 = 54.1

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Oct-2006 | Hardware Avail: Sep-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

300.twolf: -fast +FDO shlw32M.lib
BIOS Configuration Notes
Power Regulator set to Static High Performance Mode
Other Configuration Notes
Adjacent Sector Prefetch Disabled