



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## IBM Corporation

IBM System X 3550 (2.66 GHz Xeon 5150, 4MB L2 Cache)

SPECfp\_rate2000 = --

SPECfp\_rate\_base2000 = 44.9

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	54.8	67.7			
171.swim	2	205	35.1			
172.mgrid	2	146	28.7			
173.applu	2	166	29.4			
177.mesa	2	54.3	59.8			
178.galgel	2	58.5	115			
179.art	2	50.0	121			
183.quake	2	67.6	44.6			
187.facerec	2	83.7	52.6			
188.amp	2	140	36.4			
189.lucas	2	122	38.2			
191.fma3d	2	143	34.1			
200.sixtrack	2	105	24.3			
301.apsi	2	201	30.0			

### Hardware

CPU: Intel Xeon processor 5150 ( 2.66 GHz, 1333 MHz bus)  
 CPU MHz: 2667  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1, 2 chips  
 Parallel: No  
 Primary Cache: 32KB(I) + 32KB(D) on chip (per core)  
 Secondary Cache: 4096KB(I+D) on chip (per chip)  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 8 x 1024 MB ECC PC2-5300F  
 Disk Subsystem: 73GB SAS 10K RPM  
 Other Hardware:

### Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)  
 Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications  
 Build 20060323Z  
 Microsoft Visual Studio 2005(for libraries)  
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>  
 File System: NTFS  
 System State: Default

## Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M.lib
Portability:
178.galgel: -FI /F32000000
```