



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon processor E5345, 2.33 GHz

SPECfp_rate2000 = 99.2

SPECfp_rate_base2000 = 99.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2006 | Hardware Avail: Jan-2007 | Software Avail: Aug-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	129	115	8	129	115
171.swim	8	538	53.5	8	538	53.5
172.mgrid	8	335	49.8	8	335	49.8
173.applu	8	359	54.3	8	359	54.3
177.mesa	8	60.7	214	8	60.7	214
178.galgel	8	88.4	304	8	88.4	304
179.art	8	88.1	274	8	88.1	274
183.equake	8	244	49.4	8	244	49.4
187.facerec	8	135	131	8	135	131
188.amp	8	145	141	8	145	141
189.lucas	8	313	59.4	8	313	59.4
191.fma3d	8	288	67.6	8	288	67.6
200.sixtrack	8	125	81.6	8	125	81.6
301.apsi	8	241	100	8	241	100

Hardware

CPU: Intel Xeon processor E5345 (2.33 GHz, 2x4MB L2, 1333 MHz system bus)
CPU MHz: 2333
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)
Disk Subsystem: Seagate ST336754SS (SAS, 15.4krpm, 36GB)
Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10
Kernel 2.6.16.21-0.8-smp on an x86_64
Compiler: Intel C++ and Fortran Compiler 9.1 for EM64T
Build 20060816 (for 64-bit applications)
File System: ext2
System State: Multi-user runlevel 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
PASS1: -prof_gen PASS2: -prof_use

Optimization flags
ONESTEP=yes set for all benchmarks

Portability flags
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags
for Fortran and C programs: -fast +FDO

Peak tuning flags
same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon processor E5345, 2.33 GHz

SPECfp_rate2000 = 99.2

SPECfp_rate_base2000 = 99.2

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2006 | Hardware Avail: Jan-2007 | Software Avail: Aug-2006

Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

BIOS Configuration:

Adjacent Sector Prefetch = disable

This result was measured on the PRIMERGY RX300 S3. The PRIMERGY TX300 S3 and the PRIMERGY RX300 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>