



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itautec

Servidor Itautec LX211 (Intel Xeon 5150 processor, 2.66 GHz)

SPECint_rate2000 = 55.5

SPECint_rate_base2000 = 55.5

SPEC license #: 9001 | Tested by: Itautec | Test date: Nov-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	86.4	37.6	2	86.4	37.6
175.vpr	2	81.0	40.1	2	81.0	40.1
176.gcc	2	47.3	54.0	2	47.3	54.0
181.mcf	2	86.6	48.2	2	86.6	48.2
186.crafty	2	40.5	57.3	2	40.5	57.3
197.parser	2	95.5	43.7	2	95.5	43.7
252.eon	2	37.5	80.4	2	37.5	80.4
253.perlbnk	2	61.2	68.3	2	61.2	68.3
254.gap	2	45.9	55.6	2	45.9	55.6
255.vortex	2	46.5	94.8	2	46.5	94.8
256.bzip2	2	82.4	42.2	2	82.4	42.2
300.twolf	2	98.4	70.7	2	98.4	70.7

Hardware

CPU: Intel Xeon 5150 processor (2.66 GHz, 4MB L2 shared, 1333 MHz system bus)
CPU MHz: 2667
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4MB (I+D) on chip, per chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 12GB (6x2GB DDR2-RAM PC2-5300 FB-DIMM CL5 ECC)
Disk Subsystem: 1 x 120GB Serial ATA 7200 RPM
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060519Z (for 32-bit applications),
Microsoft Visual Studio 2005 (for libraries),
MicroQuill SmartHeap for SMP Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for C programs: -fast +FDO shlsMPMt.lib
for C++ programs: -fast -Qcxx_features +FDO

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library 8.0 available from
<http://www.microquill.com/>