



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itaotec

Servidor Itaotec MX201 (Intel Xeon 5150 processor, 2.66GHz)

SPECint_rate2000 = 109

SPECint_rate_base2000 = 109

SPEC license #: 9001 | Tested by: Itaotec | Test date: Nov-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	4	87.2	74.5	4	87.2	74.5
175.vpr	4	84.7	76.7	4	84.7	76.7
176.gcc	4	45.4	112	4	45.4	112
181.mcf	4	94.1	88.8	4	94.1	88.8
186.crafty	4	40.9	113	4	40.9	113
197.parser	4	90.4	92.4	4	90.4	92.4
252.eon	4	37.9	159	4	37.9	159
253.perlbnk	4	59.7	140	4	59.7	140
254.gap	4	47.5	107	4	47.5	107
255.vortex	4	48.5	182	4	48.5	182
256.bzip2	4	88.2	78.9	4	88.2	78.9
300.twolf	4	98.8	141	4	98.8	141

Hardware

CPU: Intel Xeon 5150 processor (2.66 GHz, 4MB L2 shared, 1333 MHz system bus)
 CPU MHz: 2667
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4MB (I+D) on chip, per chip, shared
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8GB (8x1GB DDR2-RAM PC2-5300 FB-DIMM CL5 ECC)
 Disk Subsystem: 1 x 36GB U320 SCSI 10000 RPM
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
 Compiler: Intel C++ Compiler 9.1
 Build 20060519Z (for 32-bit applications),
 Microsoft Visual Studio .NET 7.0.9466 (for libraries),
 MicroQuill SmartHeap for SMP Library 8.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for C programs: -fast -QxP +FDO sh1SMPMt.lib
 for C++ programs: -fast -Qcxx_features +FDO

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library 8.0 available from
<http://www.microquill.com/>