



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itautec

Servidor Itautec MX221 (Intel Xeon 5120 processor, 1.86GHz)

SPECfp_rate2000 = 34.3

SPECfp_rate_base2000 = 34.3

SPEC license #: 9001 | Tested by: Itautec | Test date: Nov-2006 | Hardware Avail: Jul-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	68.9	53.9	2	68.9	53.9
171.swim	2	252	28.6	2	252	28.6
172.mgrid	2	179	23.3	2	179	23.3
173.applu	2	204	23.8	2	204	23.8
177.mesa	2	80.8	40.2	2	80.8	40.2
178.galgel	2	80.3	83.8	2	80.3	83.8
179.art	2	64.0	94.2	2	64.0	94.2
183.quake	2	82.4	36.6	2	82.4	36.6
187.facerec	2	111	39.6	2	111	39.6
188.amp	2	201	25.4	2	201	25.4
189.lucas	2	155	29.9	2	155	29.9
191.fma3d	2	186	26.2	2	186	26.2
200.sixtrack	2	149	17.1	2	149	17.1
301.apsi	2	261	23.1	2	261	23.1

Hardware

CPU: Intel Xeon 5120 processor (1.86 GHz, 4MB L2 shared, 1066 MHz system bus)
CPU MHz: 1860
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4MB (I+D) on chip, per chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 14GB (7x2GB DDR2-RAM PC2-5300 FB-DIMM CL5 ECC)
Disk Subsystem: 1 x 120GB Serial ATA 7200 RPM
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060323Z (for 32-bit applications),
Intel Fortran Compiler 9.1
Build 20060323Z (for 32-bit applications),
Microsoft Visual Studio 2005(for libraries),
Microquill SmartHeap Library for SMP v.8.0
File System: NTFS
System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

178.galgel: -FI /F32000000

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for Fortran programs: -fast -Qansi_alias +FDO

for C programs: -fast +FDO shlsmpmt.lib

EXTRA LIBRARIES

MicroQuill SmartHeap Library for SMP v.8.0
<http://www.microquill.com/>

BIOS settings default.

The system bus runs at 1066 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.