SPEC CINT95rate Results

©Copyright 1995, Standard Performance Evaluation Corporation

BULL S.A.
EPC450 (3 CPU)

SPECint_rate95 = 493

SPECint_rate_base95 = 446

SPEC license # 20	Tested By: BULL Echirolles France	Test Date: Dec-1999	Hardware Avail: Mar-2000	Software Avail: Dec-1999



Hardware/Software Configuration for:
EPC450 (3 CPU)

Hardware

Model Name:	EPC450 (3 CPU)
CPU:	400MHz PowerPC RS64-III
FPU:	Integrated
Number of CPU(s):	3
Primary Cache:	128KBI + 128KBD on chip
Secondary Cache:	4MB(I+D) off chip
Other Cache:	None
Memory:	8192 MB
Disk Subsystem:	2 x 9.1GB Seagate ST39103LC
Other Hardware:	--

Software

Operating System:	AIX 4.3.3.0
Compiler:	IBM C/C++ Ver. 3.6.6.0
File System:	AIX/JFS, Fast SCSI
System State:	Multi-User (killall)

Benchmark # and Name	Base Copies	Base Run Time	Base SPEC Ratio	Copies	Run Time	SPEC Ratio
099.go	3	179	692	3	177	703
124.m88ksim	3	127	404	3	125	409
126.gcc	3	104	440	3	88	523
129.compress	3	104	465	3	95	510
130.li	3	125	411	3	99	519
132.ijpeg	3	210	309	3	170	382
134.perl	3	115	447	3	110	466
147.vortex	3	152	480	3	147	494
SPECint_rate_base95 (G. Mean)			446			
SPECint_rate95 (G. Mean)						493

Notes/Tuning Information

```
Base: -O4 -Q=450 -lhmu -qpdf1/2
Peak:
099: -O4 -Q=550 -qipa=noobject -lhmu -qpdf1/2
124: -O4 -Q=450 -qipa=noobject -qansialias  -qpdf1/2; fdpr -R3
126: -O -qdatalocal -qassert=addr -qinglue -qpdf1/2
-bnso -bI:/lib/syscalls.exp; fdpr -R3
129: -O3 -Q=500 -lhmu -qpdf1/2
130: -O3 -qarch=ppc -qipa=noobject -qlibansi -qpdf1/2; fdpr -R3
132: -O3 -qarch=ppc -qtune=604 -qunroll=4 -bnso
/lib/syscalls.exp
134: -O3 -qarch=ppc -qipa=noobject -Q=200 -qinglue
-Dlongjmp=_longjmp -qansialias -qunroll=4 -qpdf1/2  -bnso
-bI:/lib/syscalls.exp /usr/ccs/lib/bmalloc.o
147: -O3 -qarch=ppc -qtune=604 -qipa=noobject -Q=500 -lhm  -lhu
```