SPEC CINT95 Results

©Copyright 1995, Standard Performance Evaluation Corporation

FUJITSU LIMITED
GP7000F Model200 275

SPECint95 = 17.6

SPECint_base95 = 13.6

SPEC license # 19	Tested By: FUJITSU LIMITED	Test Date: Apr-99	Hardware Avail: Jul-99	Software Avail: Mar-99



Hardware/Software Configuration for:
GP7000F Model200 275

Hardware

Model Name:	FUJITSU GP7000F Model200 275
CPU:	272MHz SPARC64 GP
FPU:	Integrated
Number of CPU(s):	1
Primary Cache:	64KBI+64KBD on chip, 4way
Secondary Cache:	4.0MB(I+D) off chip
Other Cache:	None
Memory:	1024MB
Disk Subsystem:	2 x 9.0GB
Other Hardware:	Ethernet

Software

Operating System:	Solaris 2.6
Compiler:	Sun C5.0
File System:	UFS
System State:	Single User
Kernel Extensions:	set users_run_rmo=1, set consistent_coloring=1

Benchmark # and Name	Reference Time	Base Run Time	Base SPEC Ratio	Run Time	SPEC Ratio
099.go	4600	300	15.3	278	16.5
124.m88ksim	1900	174	10.9	101	18.8
126.gcc	1700	103	16.6	100	16.9
129.compress	1800	128	14.0	112	16.0
130.li	1900	167	11.4	112	16.9
132.ijpeg	2400	173	13.9	173	13.8
134.perl	1900	139	13.7	89	21.2
147.vortex	2700	198	13.6	124	21.7
SPECint_base95 (G. Mean)			13.6		
		SPECint95 (G. Mean)			17.6

Notes/Tuning Information

```
CULTRA= -xarch=v8plus -xcache=16/32/1:2048/64/1; MULX=-Wc,-Qiselect-imulx=1;
P1=-xprofile=collect:'pwd'/../feedback; P2=-xprofile=use:'pwd'/../feedback
Baseline: -xO4 ${MULX} -xarch=v8plus; PASS1=${P1}; PASS2=${P2}
099.go: -fast -xO5 -xsafe=mem -xrestrict -xarch=v8plus -W2,-O4+ansi_alias+cond_elim+bopt ${MULX} ${P2} -dn
124.m88ksim: -fast -xO5 -xsafe=mem -xarch=v8plus -xcrossfile -xrestrict
124.m88ksim: -W2,-O4+cond_elim+bopt+pde,-ldstr,-Mt8500 ${MULX} ${P2} -dn
126.gcc: -fast -xO4 -xarch=v8plus -W2,-ANSI_S,-Mp1,-O4+ansi_alias+cond_elim+pde,-ldstr,-Mt500
126.gcc: -Wc,-Qiselect-sw_pf_tbl_th=30 ${MULX} -xsafe=mem ${P2}
129.compress: -fast -xO5 -xsafe=mem -xarch=v8plus -xrestrict
129.compress: -W2,-O4+ansi_alias+cond_elim+pde -Wc,-Qms_pipe+unoovf ${MULX} ${P2} -dn
130.li: PASS1= -fast -xO4 -xarch=v8plus -xcrossfile ${MULX} ${P2}
130.li: PASS2= -fast -xO5 -xsafe=mem -xarch=v8plus -xcrossfile
130.li: -W2,-O4+ansi_alias+cond_elim+pde,-Mt350,-whole,-crit ${P2} -dn
132.ijpeg: -fast -xO5 -xsafe=mem  -xarch=v8plus -W2,-O4+ansi_alias+cond_elim ${MULX} ${P2} -dn
134.perl: -fast -xO4 ${CULTRA} -xcrossfile -W2,-ANSI_S,-Mp1,-O4+cond_elim
134.perl: -Wc,-Qiselect-sw_pf_tbl_th=30 ${MULX} ${P2} -lfast -dn
147.vortex: PASS1=-fast -xO4 -xarch=v8plus -xcrossfile ${MULX} ${P2}
147.vortex: PASS2=-fast -xO5 -xsafe=mem -xarch=v8plus -xcrossfile ${MULX} ${P2}
147.vortex: -W2,-O4+cond_elim,-Mt500,-Mr6000,-crit -dn
Portability: 124.m88ksim, 132.ijpeg: -DSYSV -Xc, 126.gcc: -Dalloca=_builtin_alloca -Xc; others: -Xc
Shell limits: ulimit -n 1024; ulimit -s 81920
```

For More Information Contact:
SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 20109
(703) 331-0180
info@spec.org
http://www.spec.org/

-- Prepared By: --