SPEC CINT95rate Results

©Copyright 1995, Standard Performance Evaluation Corporation

SGI Origin2100: 4X 250MHz R10k

SPECint_rate95 = 546

SPECint_rate_base95 = 539

SPEC license # 04 | Tested By: SGI | Test Date: Jul-99 | Hardware Avail: Aug-99 | Software Avail: Jul-99



Hardware/Software Configuration for:
Origin2100: 4X 250MHz R10k

Hardware

Model Name:	Origin2100: 4X 250MHz R10k
CPU:	250 MHz MIPS R10000 Processor Chip Revision: 3.4
FPU:	Integrated
Number of CPU(s):	4
Primary Cache:	32KBI + 32KBD on chip
Secondary Cache:	4MB (I+D)
Other Cache:	None
Memory:	1024MB
Disk Subsystem:	1 SCSI 4.3GB
Other Hardware:	none

Software

Operating System:	IRIX64 6.5.5
Compiler:	MIPSpro C Compiler 7.3
	IRIX Development Foundation 1.2
File System:	XFS
System State:	Multi-User

Benchmark # and Name	Base Copies	Base Run Time	Base SPEC Ratio	Copies	Run Time	SPEC Ratio
099.go	4	315	526	4	306	541
124.m88ksim	4	136	505	4	132	519
126.gcc	4	114	538	4	114	535
129.compress	4	118	549	4	117	552
130.li	4	165	413	4	161	425
132.ijpeg	4	194	445	4	189	456
134.perl	4	111	614	4	111	614
147.vortex	4	121	804	4	121	804
SPECint_rate_base95 (G. Mean)			539			
			SPECint_rate95 (G. Mean)			546

Notes/Tuning Information

```
Portability Flags: all: -DUSG  gcc: -Dalloca=__builtin_alloca
FEEDBACK:
.   PASS1 = -fb_create /tmp/FBDIR/$(EXENAME)
.   PASS2 = -fb_opt /tmp/FBDIR/$(EXENAME)
Base Flags: -Ofast=ip27 -IPA:use_intrinsic, FEEDBACK
Peak Flags:
go:       -O2 -n32 -mips4 -IPA:plimit=1000:small_pu=60:use_intrinsic \
.         -TARG:platform=ip27 -OPT:Olimit=0 -OPT:goto=off, FEEDBACK
m88ksim:  -O2 -TARG:platform=ip27 -IPA:plimit=4000:space=100:small_pu=90:use_intrinsic \
.         -OPT:Olimit=0:ro=3:goto=off:unroll_times_max=32:unroll_size=300, FEEDBACK
gcc:      -Ofast=ip27 -IPA:use_intrinsic, FEEDBACK
compress: -Ofast=ip27 -IPA:use_intrinsic, FEEDBACK
li:       -Ofast=ip27 -IPA:use_intrinsic:min_hot=12:callee_limit=750:plimit=12000 \
.         -IPA:space=200:clone=on:aggr_cprop=on -OPT:goto=off, FEEDBACK
ijpeg:    -Ofast=ip27 -LNO:fission=0:interchange=off:pf2=0:ou_max=2 -OPT:unroll_analysis=off:unroll_size=480:ieee_arith=3 \
.         -IPA:use_intrinsic:callee_limit=950:plimit=730:space=130:clone=on -OPT:goto=off, FEEDBACK
perl:     -Ofast=ip27 -IPA:use_intrinsic, FEEDBACK
vortex:   -Ofast=ip27 -IPA:use_intrinsic, FEEDBACK
.
Large pages were enabled for base and peak using:
.  systune -i ;  percent_totalmem_1m_pages = 50 ; nlpages_1m = 400
.  setenv PAGESIZE_DATA 1024
```

For More Information Contact:
SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 20109
(703) 331-0180
info@spec.org
http://www.spec.org/

-- Prepared By: --